

Automatic Screen Printing Press



M&R's COBRA E™ automatic screen printing presses set the standard in combining quality components, durable craftsmanship and high speed production all in one machine.

The COBRA series of presses provide operators with time-saving features needed for quick setups—electric printheads, tool-free squeegee/floodbar angle adjustments with air locks, pneumatic frame locks, and independent squeegee/flood speeds with digital displays. The flat-indexing system is also digital-compatible on most models. COBRA presses are Tri-LOC® and Tri-Sync™ compatible—like all M&R presses—which further minimizes setup times, and maximizes run times and productivity.

Multiple configurations and maximum image areas mean that there is sure to be a COBRA E that meets your needs. You can rest assured that whichever you choose, M&R has you covered with best-in-class design, service and support.

FEATURES

- Robust, flat indexing system
- Smooth, quiet operation
- Pneumatic-locking, Quick-Flip™ Front Frame Holders
- Slimline pallet-leveling adjustment system provides simpler adjustment
- Upgraded precision front and rear micro-registration controls
- Simple front and rear on-head/off-contact controls
- New membrane switch-based printhead controls enable quicker setup and enhanced repeatability
- Maintenance Minder™ System with photos and descriptions alerts operators when scheduled maintenance is due
- HMI interface features Heads Idle Mode and updated Revolver Print Program™

Find more information and where to buy at: www.mrprint.com



Flat-Indexing System • Smooth, Quiet Operation • Digital-Ready*

The COBRA E features a 7.5" high-resolution touchscreen interface with easy-to-learn logic and enhanced icon graphics. Built-in tutorial screens give quick onscreen access to multi-language setup guides. The operating instructions effectively put a user's manual at the operator's fingertips. The intuitive icon-based interface simplifies operator training.



User-friendly touchscreen interface provides ease of use



Pneumatic-locking, Quick-Flip™ front frame holders



Individual membrane switch controls enable quicker setups

* Digital-ready compatibility available on most COBRA models—contact M&R Printing Equipment, Inc. for details.

SPECIFICATIONS	Cobra E 1618 10/8	Cobra E 1618 12/10	Cobra E 1618 14/12	Cobra E 2020 10/8	Cobra E 2020 12/10	Cobra E 2020 14/12
Air @ 6,9 bar (100 PSI)	227 l/min (8 cfm)	283 l/min (10 cfm)	340 l/min (12 cfm)	227 l/min (8 cfm)	283 l/min (10 cfm)	340 l/min (12 cfm)
Electrical Requirements ¹	208/230 V, 1 ph, 38 A, 50/60 Hz, 3.9 kW 208/230 V, 3 ph, 22 A, 50/60 Hz, 3.9 kW 380/415 V, 3 ph, 11 A, 50 Hz, 3.9 kW	208/230 V, 1 ph, 43 A, 50/60 Hz, 4.6 kW 208/230 V, 3 ph, 28 A, 50/60 Hz, 4.6 kW 380/415 V, 3 ph, 14 A, 50 Hz, 4.6 kW	208/230 V, 1 ph, 48 A, 50/60 Hz, 6 kW 208/230 V, 3 ph, 34 A, 50/60 Hz, 6 kW 380/415 V, 3 ph, 17 A, 50 Hz, 6 kW	208/230 V, 1 ph, 38 A, 50/60 Hz, 8.7 kW 208/230 V, 3 ph, 22 A, 50/60 Hz, 8.7 kW 380/415 V, 3 ph, 12 A, 50 Hz, 8.7 kW	208/230 V, 1 ph, 48 A, 50/60 Hz, 11.2 kW 208/230 V, 3 ph, 28 A, 50/60 Hz, 11.2 kW 380/415 V, 3 ph, 16 A, 50 Hz, 11.2 kW	208/230 V, 1 ph, 58 A, 50/60 Hz, 11.1 kW 208/230 V, 3 ph, 34 A, 50/60 Hz, 13.5 kW 380/415 V, 3 ph, 19 A, 50 Hz, 13.5 kW
Diameter	384 cm (12' 7")	429 cm (14' 1")	470 cm (15' 5")	432 cm (14' 2")	478 cm (15' 8")	521 cm (17' 1")
Maximum Frame Size	58 x 84 x 5 cm (23" x 33" x 2")	58 x 84 x 5 cm (23" x 33" x 2")	58 x 84 x 5 cm (23" x 33" x 2")	66 x 91 x 5 cm (26" x 36" x 2")	66 x 91 x 5 cm (26" x 36" x 2")	66 x 91 x 5 cm (26" x 36" x 2")
Maximum Image Area	41 x 46 cm (16" x 18")	41 x 46 cm (16" x 18")	41 x 46 cm (16" x 18")	51 x 51 cm (20" x 20")	51 x 51 cm (20" x 20")	51 x 51 cm (20" x 20")
Shipping Weight	1928 kg (4250 lb)	2495 kg (5500 lb)	2903 kg (6400 lb)	2260 kg (4980 lb)	2590 kg (5710 lb)	3007 kg (6630 lb)
Standard Pallet Size	41 x 56 cm (16" x 22")	41 x 56 cm (16" x 22")	41 x 56 cm (16" x 22")	41 x 56 cm (16" x 22") 56 x 63 cm (22" x 25")	41 x 56 cm (16" x 22") 56 x 63 cm (22" x 25")	41 x 56 cm (16" x 22") 56 x 63 cm (22" x 25")
Stations/Colors	10/8	12/10	14/12	10/8	12/10	14/12

¹ If incoming voltage differs from the voltage(s) listed in this brochure, calculate amperage accordingly. Other electrical configurations are available: contact M&R Printing Equipment, Inc. for details.

M&R Printing Equipment, Inc. 440 Medinah Road, Roselle, Illinois 60172-2329 USA www.mrprint.com
USA: 800-736-6431 / 630-858-6101 • Outside USA: +1-847-967-4461 • FAX: 630-858-6134

M&R Printing Equipment, Inc. and its subsidiaries (hereinafter M&R), believe the information in this advertisement to be accurate at publication, though it does not purport to list all manufacturing and specification variations, nor does it assume liability resulting from incompleteness or inaccuracy. M&R reserves the right to change specifications without notice. M&R expressly disclaims any liability for damages, consequential or incidental, from purchase, installation, servicing, and/or use of any product/service based upon information herein. No warranties of merchantability or fitness for a particular purpose are made or are to be implied from the information herein. No information herein may be reproduced or used in any manner without the prior, express written consent of M&R in each case. Copyright 2023 M&R Printing Equipment, Inc. All rights reserved. 20230612