

# EASISOLV 140

## SOLVENT CLEANER

EasiSolv 140 Solvent Cleaner is designed to effectively break down and dissolve all types of printing inks from screen mesh, squeegees, flood bars, pad printing cliches, ink scrapers, tools, frames, and presses. This product has a flash point of over 140°F, making it safer and simpler to dispose of compared to lower flash, volatile solvents.

<b>Appearance:</b>	Clear
<b>Odor:</b>	Aromatic
<b>Ph:</b>	Neutral
<b>Flash Point:</b>	61°C / 142°F
<b>Specific Gravity:</b>	0.92-0.93 @ 20°C / 68°F
<b>Weight/gl:</b>	7.7 lbs/gallon
<b>VOCs:</b>	930 grams/liter
<b>Dot Shipping:</b>	Non-hazardous

<b>Quart</b>	140-1 QT
<b>Gallon</b>	1401-1 GL
<b>5 Gallon pail</b>	140-5 GL
<b>55 Gallon Drum</b>	140-55 GL

### STORAGE REQUIREMENTS

Keep the container tightly closed. Store in a dry, cool and well ventilated place away from incompatible materials such as oxidizing agents and acids.

### PRODUCT FEATURES

- High flash point
- Longer evaporation time
- Good adhesive remover
- Non-hazardous
- Low to no odor

### APPLICATION/USE

Scrape excess ink from the screen. Apply EasiSolv 140 by squirt bottle, pneumatic sprayer, or rag to the (well) ink side of the screen. Thoroughly agitate ink with a rag or a scrubber, then wipe up all the dissolved ink with a shop rag on both sides. Reapply if necessary and follow with a dry rag.

### COMPATIBLE INK TYPES

- Plastisol
- UV/Solvent
- Conductive
- Industrial