

PLASTISOLV 842

ON PRESS CLEANER/PRESS WASH

PlastiSolv 842 On Press Cleaner removes plastisol inks and quickly dries during on press applications. 842 is to be used on your production floor during on press color changes, saved screens, removing ink from squeegees, floodbars, and other equipment.

Appearance:	Clear
Odor:	Citrus
Ph:	Neutral
Flash Point:	61°C / 113°F
Specific Gravity:	0.80 @ 20°C / 68°F
Weight/gl:	6.4 lbs/gallon
VOCs:	800 grams/liter
Dot Shipping:	Non-hazardous

Quart	842-1 QT
Gallon	842-1 GL
5 Gallon pail	842-5 GL
55 Gallon Drum	842-55 GL

STORAGE REQUIREMENTS

Keep the container tightly closed. Store in a dry, cool and well ventilated place away from incompatible materials such as oxidizing agents and acids.

PRODUCT FEATURES

- Best used for textile applications
- High flash point
- Non-flammable
- Non-hazardous
- Safe for squeegees & floodbars
- Can be used in a recirculating system

APPLICATION/USE

Scrape excess ink from the screen. Apply PlastiSolv 842 by squirt bottle, pneumatic sprayer, or rag to the (well) ink side of the screen. Thoroughly agitate ink with a rag or a scrubber, then wipe up all the dissolved ink with a shop rag on both sides. Reapply if necessary and follow with a dry rag.

COMPATIBLE INK TYPES

- Plastisol